

# MATERIAL SAFETY DATA SHEET

## SECTION 1 - IDENTIFICATION

### CREAPEN

**Trade Name:** Willi Geller Creation® Creapen

**Product Use:** Dental ceramics

**Product Names(S):** Creapen

**Emergency Telephone:** 1-800-243-2000

**Importer/Supplier:** Jensen Dental  
50 Stillman Road  
North Haven, CT, 06473

**Revised:** July 29, 2009

## SECTION 2 - HAZARD IDENTIFICATION

The hazards listed below may occur if the PELs and/or TLVs exceed the constituent's established values listed in section 3:

**Paraffin (wax fume):** Contact with the eyes or skin may result in irritation. Inhalation of this material may cause irritation to the respiratory system; nausea

## SECTION 3 – COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

COMPONENT	%RANGE	CAS#	*PEL/OSHA (mg/m <sup>3</sup> )	**TLV/ACGIH (mg/m <sup>3</sup> )
Paraffin Mixture of natural and synthetic-waxes, resins, and pigments:	N/A	N/A	N/A	N/A
Paraffin (wax fume):	N/A	8002-74-2	<sup>a</sup> 2	<sup>a</sup> 2

<sup>a</sup>= Fume only

\*Taken from the Permissible Exposure Limits for Air Contaminants established by OSHA CFR 29 1910.1000 Subpart Z – Toxic and Hazardous Substances

\*\*Taken from the ACGIH Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices

## SECTION 4 - FIRST AID MEASURES

**Inhalation:** Breathing difficulty caused by inhalation of this material requires immediate removal to fresh air. There are no known cases in which a person stopped breathing as a result of exposure. If breathing has stopped, perform artificial respiration and obtain medical assistance.

**Ingestion:** Swallowing this material can be treated by having the affected person drink large quantities of water. If this method proves ineffective, immediately obtain medical assistance.

**Skin:** Skin cuts and abrasions should be treated by standard first aid. Skin contamination with material can be removed by washing with soap and water. Obtain medical help if irritation develops and persists.

**Eyes:** material should be flushed from the eyes with a lot of clean water. Obtain medical help if irritation persists.

## SECTION 5 - FIRE FIGHTING MEASURES

**Flash Point (°C):** ~230

**Explosive Limits (% in Air):** Lower: N/A Upper: N/A

**Extinguishing Media:** Use fire fighting measures that suit the environment: Foam, CO<sub>2</sub>, extinguishing powder, or water jet.

**Fire & Explosion Hazards:** Fire can cause release of nitrogen oxides (NO<sub>x</sub>) and ammonia (NH<sub>3</sub>).

**Special Fire Fighting Procedures:** The development of hazardous combustible gases and/or vapors may occur during a fire



### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Steps to Be Taken If Material Is Released or Spilled:** Establish a restricted entry zone based on the severity of the spill. Persons entering the restricted zone must wear adequate respiratory protection and protective clothing appropriate for the severity of the spill. Use gloves for molten material. Use a liquid-absorbent material to clean up released material.

### SECTION 7 - HANDLING AND STORAGE

**Handling:** Wear an approved respirator when melting this product (see section 8).

**Storage:** Store material in original container at room temperature, and avoid direct light.

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Respiratory Protection:** When potential exposures are above the occupational limits shown in Section 2, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional.

**Other Protective Equipment:** None

**Gloves:** Rubber or latex gloves recommended when working with molten material.

**Eye Protection:** Wear safety glasses (goggles)

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Color:</b> Clear	<b>Melting Point (°C):</b> N/A	<b>Density (g/cm<sup>3</sup>):</b> 0.88	<b>Boiling Point (°C):</b> 300-500
<b>Evaporation Rate:</b> N/A	<b>Freezing Point:</b> N/A	<b>Odor:</b> none	<b>pH-value:</b> N/A
<b>Physical State:</b> Liquid	<b>Radioactivity:</b> N/A	<b>Solubility:</b> insoluble in water	<b>Sublimes At:</b> N/A
<b>Vapor Density (Air = 1):</b> ~100-230 mPa	<b>Vapor Pressure (at 20°C):</b> < 0.0001 hPa	<b>% Volatiles by Volume:</b> N/A	

### SECTION 10 - STABILITY AND REACTIVITY

**General Reactivity:** This material is stable. **Noncompatibility With Other Substances:** Strong acids and oxidizing agents

**Hazardous Combustion Products:** None under normal conditions of use. **Hazardous Polymerization:** Will not occur.

### SECTION 11- TOXICOLOGICAL INFORMATION

#### **PRIMARY ROUTES OF EXPOSURE:**

**Inhalation:** Inhalation of materials' fumes can cause irritation to the skin, throat, respiratory system, and the conditions listed in section 2.

**Ingestion:** There are no known cases of illness resulting from ingestion of this material. Ingestion can occur from material contamination involved with hand to mouth activities such as eating, drinking, smoking, nail biting, etc. These products are not intended for internal consumption. As a standard hygiene practice, hands should be washed before eating or smoking.

**Skin:** Contact with molten wax will cause thermal burns. Skin contact with this material may cause, in some sensitive individuals, dermatitis/irritation. Skin abrasion may cause irritation. See Section 4 for additional information.

**Eyes:** Contact with molten wax will cause thermal burns. Injury can result from particulate irritation or mechanical injury to the eyes by dust or particulate. Exposure may result from direct contact with airborne particulate (dust or powder) or contact to the eye of contaminated hands or clothing.

**EFFECTS OF OVEREXPOSURE:**

**The potential health effects listed below are confined to constituents which are in sufficient concentrations within the product to be significant.**

**Acute** (*immediate or near-term health effects*): Irritation to eyes and skin may result from short-term exposure. LD50 (oral, rat) > 2000 mg/kg

**Chronic** (*long-term health effects*): There are no known chronic effects associated with this material.

**CARCINOGENIC REFERENCES:**

**NTP:** None

**IARC:** None

**NIOSH:** None

**ACGIH:** None

**Medical Conditions Aggravated By Exposure:** None

**SECTION 12- ECOLOGICAL INFORMATION**

This material is insoluble in water. There is no information available on the ecological effects of this material.

**SECTION 13- DISPOSAL CONSIDERATIONS**

**Waste Management:** Comply with Federal, State, and local regulations.

**SECTION 14 - TRANSPORT INFORMATION**

There are no U.S. Department of Transportation hazardous material regulations that apply to the packaging and labeling of this product as shipped by Jensen Industries Inc.

**SECTION 15- REGULATORY INFORMATION**

**OSHA Hazard Communication Standard, 29 CFR 1910.1200:** Components of these products are considered hazardous ingredients.

**Wastewater:** Wastewater regulations can vary considerably. Contact your local and state governments to determine their requirements.

**Other Regulations, Limitations and Prohibitive Regulations:** N/A

**SECTION 16 - OTHER INFORMATION**

This data is based on our present knowledge. However, that shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This MSDS has been revised following the guidelines outlined in CFR 1910-1200 "Material Safety Data Sheets."

**Important: If you have any questions or require additional information regarding the materials described in this Material Safety Data Sheet please contact Jensen Dental at 1-(800) 243-2000.**